

Product Feature



New Generation Optical Path Design

New core technology of fiber gain control



High Output Power

Greatly improved single pulse energy



Compact and Rugged Design

Maintenance free Operation



Wide Application Even with Highly Reflective Material

High performance isolator effectively reduces reflection damage to the laser source Smoothly marking on aluminum, copper and brass etc



High Level Vertical Integration

All key components are designed and produced in house Strict quality control, high consistency and reliability



MFPT 100~300M+ Fiber Laser Specifications

	MEDT 100 M.	MEDT 120 M	MEDT 150 M.	MEDT 200 M.	MEDT 250 M	MEDT 200 M.
Models	MFPT-100 M+	MFPT-120 M+	MFPT-150 M+	MFPT-200 M+	MFPT-250 M+	MFPT-300 M+
OPTICAL SPECIFICATIONS						T
Nominal Power	≥ 100W	≥ 120W	≥ 150W	≥ 200W	≥ 250W	≥ 300W
Mode of Operation	Pulse & Continuous					
Polarization	Random					
Power Tunability	10 to 100%					
Wavelength	1060~1070nm					
Power Stability	<5 %					
Laser Beam Quality M2	<1.6, typical value 1.3					
Pulse Energy	1.8 mJ					
Pulse Duration	10~500 ns					
Repetition Rate	1~4000 kHz					
	DELIVERY SYSTE	M				
Length	5m standard, other lengths optional					
Beam Diameter	5~7mm				8±1mm	
	ELECTRICAL RATINGS					
Supply Voltage	220 VAC Single-phase					
	OTHER SPECIFICATIONS					
Operating Temperature	0 to +40°C					
Storage Temperature	-10 to +60°C					
Humidity	10 to 95%					
Cooling Method	Air Cooling					
Dimension	490.4×422×131.3 mm					
Weight	25 kg					

Mechanical Specifications (mm)

